



## “B” Series UVC Light (Kitchen Hood Style)



产品型号 Name	灯管功率 lamp watt	管数 quantity	管径 Diameter (mm)	管长 length (mm)	设备尺寸 Module size (L-W-H:mm)	适用烟罩 Hood (m)	长寿命涂层 LONG-LIFE	变频光解 POWER-LIGHT	风速 air speed (m/s)
H2	38W	4	15	790	932*305*78	1m	Y	N	2
H3	58W	4	15	1200	1376*305*78	1.5m	Y	N	2
H4	79W	4	15	1630	1769*305*78	2m	Y	N	2
H2S	64W	4	19	793	932*305*78	1m	Y	Y	2.5
H3S	98W	4	15	1200	1376*305*78	1.5m	Y	Y	2.5
H4S	135W	4	19	1630	1769*305*78	2m	Y	Y	2.5
H2T	64W	6	19	793	932*360*78	1m	Y	Y	2.5
H3T	98W	6	19	1200	1376*360*78	1.5m	Y	Y	2.5
H4T	135W	6	19	1630	1769*360*78	2m	Y	Y	2.5
H2SE	71W	4	19	875	1051*305*78	1m	Y	Y	2.5
H3SE	82W	4	19	1000	1176*305*78	1.5m	Y	Y	2.5

**Noted: Model H2S, H3S, H4S, H2T, H3T, H4T, H2SE & H3SE  
(On special request, subjected to factory confirmation)**



## “B” Series UVC Light (Kitchen Hood Style)



### Model & Specification of Control Box

电控箱型号 Model	模块尺寸 Module Size (L-W-H: mm)	最多控制灯架数量 Max. Controlled Support	功能 Air Speed (m/s)
B10	230*130*360	5	开启、停止、运行计时、风机联动 Startup, Stop, Operation Timing, Fan Linkage
B50	300*125*410	5	单片机控制、LCD 显示, 风机联动, BA 控制, 挡板与消防联动 Single Chip Control, LCD Display, Fan Linkage, BA Control, Baffle and Firefighting Linkage
B30PL	280*153*916	2	PLC 控制, 液晶触摸显示, 风机联动, BA 控制, 挡板与消防联动 PLC Control, LCD Touch Display, Fan Linkage, BA Control, Baffle and Firefighting Linkage
B60PL	280*153*916	5	PLC 控制, 液晶触摸显示, 风机联动, BA 控制, 挡板与消防联动 PLC Control, LCD Touch Display, Fan Linkage, BA Control, Baffle and Firefighting Linkage

**Noted: Model B50, B30PL & B60PL (On special request, subjected to factory confirmation)**