





## “B” Series UVC Light (Cabinet Style)

Model/ Specification	H32M/H	H40M/H	H48M/H	H54M/H	H64M/H	H72M/H
处理风量 (CMH) Treated Air Flow	32000m <sup>3</sup> /h	40000m <sup>3</sup> /h	48000m <sup>3</sup> /h	54000m <sup>3</sup> /h	64000m <sup>3</sup> /h	72000m <sup>3</sup> /h
处理效率 (%) Treatment Efficiency	90%	90%	90%	90%	90%	90%
压损 (pa)	≤100	≤100	≤100	≤100	≤100	≤100
机台尺寸 (mm) Dimension of Bench (L x W x H)	570* 1600*1300	570* 1600*1935	570* 2180*1300	570*3200*1300	570*3200*1300	570*2180*1950
法兰口径 (mm) Caliber of Flange	1380*1065	1380*1715	1850*1065	2870*1065	2870*1065	1850*1715
重量 (kg) Weight	192	208	268	369	382	402
灯管数量 UV Quantity	24	32	48	40	48	60
风管长度 (mm) UV Length	1000	1000	800	1000	1000	800
使用电压 Used Voltage	220VAC50HZ	220VAC50HZ	220VAC50HZ	220VAC50HZ	220VAC50HZ	220VAC50HZ
功率 (kw) 普通 Power (Ordinary)	1.2	1.6	1.9	2	2.5	2.85
保养空间 (mm) Maintenance Space	1100	1100	900	1100	1100	900